

ROBESON SEWING MACHINE COMPANY









1126 HARPETH IND. CT., FRANKLIN, TENNESSEE 37064 USA













800-422-3330 / 615-790-2222 / 615-791-1241(FAX)

website: www.robessonsew.com / email: robesson@bellsouth.net

SPECIAL OFFERING ON REBUILT



Model								
	Lock stitch	Max. stitch length (mm)	Shuttle hook	Sewing area X-Y (mm)	Max. number of stitches	Thread trimmer	Wiper	Max. sewing speed (spm)
LK3-B430E	★	0.1 - 10.0	★	30 × 10	5,000	★	★	2,500

Subclass	Program No.	Sewing pattern	No. of stitches	Standard bar tacking length	Standard bar tacking width
1	01		42	16 mm	2 mm
	04		30	16 mm	2 mm
5	05		29	10 mm	2 mm
	08		21	7 mm	2 mm
2	02		42	20 mm	3 mm
	03		35	20 mm	3 mm
	06		29	16 mm	3 mm
7	07		28	8 mm	2 mm
	09		21	7 mm	2 mm
	10		21	10 mm	—
	11		28	10 mm	—
	12		28	20 mm	—

Main use
 Jeans · · · Belt loop attachment, pocket top, front, crotch
 Slacks · · · Belt loop attachment, side-pocket top, rear pocket, front
 Jackets, foundation garments, underwear, etc.