

# ROBESON SEWING MACHINE COMPANY

1126 HARPETH IND. CT., FRANKLIN, TENNESSEE 37064 USA

800-422-3330 / 615-790-2222 / 615-791-1241(FAX)

website: www.robessonsew.com / email: robesson@bellsouth.net

**\*SPECIAL OFFERING ON REBUILT\***



## ● SPECIFICATIONS

### AMS-210C

Stitch type .....	1-needle lockstitch
Sewing size .....	<b>Max. 60mm (2-7/16") (L) x 125mm (4-59/64") (w)</b>
Sewing speed .....	Max. 2,000 s.p.m. (for stitch length of 3 mm or less)
Stitch length .....	<b>0.1 to 12.7mm</b>
Feeding frame lift .....	Max. 22mm (55/64")
Needle .....	DP x 5 #14 (Standard model) DP x 17 (model for medium- to heavy-weight material)
Hook .....	Special large shuttle hook
Input device .....	Provided as standard device (can be also connected to the PGM-1, PGM-5 of the compact type programming device)
Memory medium .....	2DD 3.5-inch micro floppy disk
Number of stitches .....	Max. 176,000 stitches (Max. 4,000 stitches a pattern)
Number of patterns .....	Max. 691 patterns
Enlargement/Reduction .....	<b>0.1 to 400% (increasing or decreasing either the number of stitches or stitch length)</b>
Origin positioning .....	Free origin setting method
Safety feature .....	<b>Stop switch and error code indication in case of thread breakage or erroneous operation</b>
Power requirements .....	Single-phase or 3-phase (1K VA)
Weight .....	150kg
Dimensions .....	Length 660mm x width 1,200mm x height 1,130mm
<b>AMS-210CGL</b>	<b>Double-capacity shuttle hook type for heavy-weight materials</b>
Needle .....	DP x 17 #23 (provided at the time of delivery)
Hook .....	Special-purpose, double-capacity shuttle hook
Compressed air .....	5.5kg/cm <sup>2</sup> , 1.8 l/min.
Motor .....	550W 2P E motor