

ROBESON SEWING MACHINE COMPANY

1126 HARPETH IND. CT., FRANKLIN, TENNESSEE 37064 USA

800-422-3330 / 615-790-2222 / 615-791-1241(FAX)

website: www.robessonsew.com / email: robesson@bellsouth.net

SPECIAL OFFERING ON REBUILT



● SPECIFICATIONS

AMS-220C

Stitch type	1-needle lockstitch
Sewing size	Max. 145mm (5-45/64") (L) x 200mm (7-7/8") (W)
Sewing speed	Max. 2,000 s.p.m. (for stitch length of 3 mm or less)
Stitch length	0.1 to 12.7 mm
Lift of the intermediate presser	Max. 2 mm
Stroke of the intermediate presser	Standard 4mm (can be adjusted within the range from 0, 3 to 7mm)
Feeding frame lift	(pneumatic type) Max. 25mm (63/64") Standard 22mm (55/64")
Needle	DP x 5 #14 (standard model)/ DP x 17 (model for medium- to heavy-weight material)
Sewing hook	Semi-rotary large hook
Input device	Provided as standard device (can be also connected to the PGM-5A or PGM-1 of the compact type programming device)
Memory medium	2DD 3.5-inch micro floppy disk
Number of stitches	176,000 stitches can be stored in a cassette
Number of patterns	44 to 691 patterns can be stored in a cassette (within 4,000 stitches per pattern)
Enlargement/Reduction	0.1 to 400% (increasing or decreasing either the number of stitches or stitch length)
Safety feature	Stop switch and error code indication in case of thread breaking or erroneous operation
Compressed air	5.5 kg/cm ² 1.8 Ni/min.
Power requirements	Single-phase/3-phase (1K VA)
Dimensions	1,090mm (W) x 1,10 mm (L) x 1,150mm (H)
Weight	270kg